



TTQ-143 Fall Framed – Pattern Corrections:

Cutting Instructions

We found an error in our cutting instruction for Fall Framed and sincerely apologize for any inconvenience this will cause.

The new cutting instruction read:

PANEL-C8520 Cream Fabric:

- Trim to 23-inch x 34 -inch.

Wood-CM8527 Cream Fabric:

- Cut four 2-inch x WOF strips. Subcut two 2-inch x 23-inch strip and two 2-inch x 34-inch strip.

Shimmer-Rust Fabric:

- Cut four 1 ½-inch x WOF strips. Sew the strips together end to end. Subcut into two 1 ½-inch x 42 ½-inch strips (Long Border) and two 1 ½-inch x 34-inch strips (Short Border).
- Cut one 2-inch x WOF strip. Subcut sixteen 2-inch x 1 ¾-inch rectangles (16 Piece B).

Shimmer-Ivory Fabric:

- Cut one 2-inch x WOF strip. Subcut four 2-inch squares (4 Piece C).

The new assembly instruction read:

1. Sew Moss Strip to Honey Strip to make eight 1 ¾-inch x WOF strips. Subcut strips into four 1 ¾-inch x 34-inch honey/moss strips, four 1 ¾-inch x 24-inch honey/moss strips, and thirty-two 1 ¾-inch x 1 1/8-inch honey/moss pieces
4. Sew Rust Piece B to two opposite sides of Ivory Piece C. (Make 4 Unit 2).
6. Sew two 1 ¾-inch x 23-inch honey/moss strips to two opposite sides of Wood 2-inch x 23-inch strip. Make two Short strips
8. Sew two 1 ¾-inch X 34-inch honey/moss strips to two opposite sides of Wood 2-inch x 34-inch strip. Make two Long strips.
13. Press the center and trim to 32-inch x 43-inch.