

TTQ-234 Sew Wonderful – Pattern Corrections:

Cutting Instructions

We found errors in our cutting instruction and sincerely apologize for any inconvenience this will cause.

Additions are given in red. Deletions are struck through.

Era-CD1501 Grey:

- **Cut** one 97-inch x WOF strip. **Subcut** two 7-9-inch x 1210 1/2-inch rectangles (Pieces L5 and M5) and two 6-inch x 8-inch rectangles (Pieces F3 and H3).
- **Cut** one 6-inch x WOF strip. **Subcut** two 6-inch squares x 7-inch rectangles (Pieces K4 and J4) and 5 ½-inch x 13 ½-inch strips (Pieces A1 and B1).
- **Cut** one 5-inch x WOF strip. **Subcut** two 5-inch squares (Pieces K2 K1 and J2J1), two 4 ½5-inch x 2 ½-inch rectangles (Pieces C2 and E2D2), and two 4-inch x 7-inch rectangles (Pieces C5 and D5).
- **Cut** one 3-inch x WOF strip. **Subcut** two 3-inch x 6-inch rectangles (Pieces A3 and D3B3), two 3-inch x 5 ½-inch rectangles (Pieces C4 and D4), one 3-inch x 1½-inch rectangle (Piece H4) and two 2 ½-inch x 7-inch strips (Piece I1 and I3).
- **Cut** one 2 ½-inch x WOF strip. **Subcut** two 2 ½-inch x 5-inch rectangles squares (Pieces L1 and M1), two 2 ½-inch squares (Pieces C2 and D2), two 2-inch x 3-inch rectangles (Pieces F1 and H1), and two2-inch x 45-inch strips (Pieces L3 and M3).
- Cut two 1-inch x WOF strips. Subcut eight 1-inch x 6 ½-inch strips. (Spool border)
- Cut five 1 inch x WOF strips. Sew strips together end to end. Subcut two 1 inch x 43 ½ inch strips and two 1-inch x 55 ½-inch strips. (Border 2)

Mix-C7200 Charcoal:

• **Cut** one 3 ½-inch X WOF strip. **Subcut** two 3 ½-inch x 4-inch rectangles (Piece C1 and D1) and one 3-inch x 1½-inch rectangle (Piece H4).

Dress Form:

- 5) Make Section C (Figure 3)
 - a) Using the FTSP method, assemble Section C in order, starting with C1 and ending with C56.
- 6) Make Section D (Figure 4)
 - a) Using the FTSP method, assemble Section D in order, starting with D1 and ending with D56.
- 11) Make Section K (Figure 9)
 - a) Using the FTSP method, assemble Section K₁ in order, starting with K1 and ending with K4.



- 12) Make Section L (Figure 10)
 - a) Using the FTSP method, assemble Section Li in order, starting with L1 and ending with L6.
- 13) Make Section M (Figure 11)
 - a) Using the FTSP method, assemble Section MJ in order, starting with M1 and ending with M6.
- 14) Assemble **Dress Form**. (Figure 12 and Figure 13)
 - d) Sew Section J and Section K together to form Section JK.
 - f) Working from the top downward, sew sections together in the following order: Piece G1, Section FH, Section CD, Section AB, Section I, Section LMN, Section JK and Piece E1.
- 16. Sew together five **Spool Blocks** and four CD1501 Grey 1-inch x 6 ½-inch Strips, alternating, to make **Spool Strip**. Arrange Spools to alternate directions as shown in Figure 17. Make two **Spool Strips**. Strip should be 6 ½-inch x 33 ½-inch. (Figure 17)
- 17) Sew 20 ½-inch x 39 ½-inch panel to left side of Dress Form. Press to make Quilt Center, which should measure 33 ½-inch x 39 ½-inch.
- 18) Assemble Quilt Center by sewing strips together in order listed below. Note orientation of strips. (Figure 18)
- a) Spool Strip
- b) Black 1 ½-inch x 33 ½-inch strip
- c) Center
- d) Black 1 ½-inch x 33 ½-inch strip
- e) Spool Strip
- 19) Add borders.
 - a) Sew Black 1 ½-inch x 5339 ½-inch strips to sides of quilt center. Then, sew Black 1 ½-inch x 35 ½-inch strips to top and bottom of quilt center.